

Polyaluminium Chloride

UN3264 CORROSIVE LIQUID,
ACIDIC, INORGANIC, N.O.S.
(ALUMINIUM CHLORIDE HYDROXIDE SULPHATE)

Polyaluminium Chloride
PAX XL6



C US
Tested and Certified by WQA
against NSF/ANSI 60
23.0 kg

MUL 250 mg/l

Technical product for
use at water
treatment plants

DO NOT FILL ANYTHING INTO THIS CANISTER WHEN EMPTY
DO NOT TRANSFER RESIDUES INTO OTHER CONTAINERS
RETURN EMPTY CANISTER TO OSORNO

Polyaluminium Chloride - PAX XL6

Refer to Material Safety Data Sheet

Caution: CORROSIVE



Health hazard:

Harmful if swallowed.
Cause severe burns to skin and eyes.
May cause delayed lung injury if inhaled.

Precautions:

Avoid all contact.
Avoid prolonged or repeated breathing
of vapour.
Do not take internally.
Wash thoroughly after handling.
Wear protective equipment and clothing.



First aid:

In all cases, obtain medical attention.
Flush with water for at least 20 minutes.
If swallowed give water to dilute.
Do not induce vomiting.
If inhaled, move victim to fresh air.

**In case of a dangerous
goods emergency call
Osorno
204-488-1538**

OSORNO Enterprises Inc.
976 Elgin Ave.
Winnipeg, MB R3E 1B4
Canada